

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DOS Thread Locking Agent medium 50g

Version 4.12 Revision Date: 09.11.2020 SDS Number: 576365-00006 Date of last issue: 05.05.2020
Date of first issue: 21.12.2009

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : DOS Thread Locking Agent medium 50g
Product code : 0893 243 050

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Adhesives
Professional use product

1.3 Details of the supplier of the safety data sheet

Company : Würth UK Ltd
1 Centurion Way
Erith, Kent

Telephone : +44 (0)3300 555 444
Telefax : +44 (0)3300 555 666
E-mail address of person responsible for the SDS : prodsafe@wuerth.com

1.4 Emergency telephone number

+44 (0)870 190 6777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Long-term (chronic) aquatic hazard, Category 3 H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard statements : H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P273 Avoid release to the environment.

2.3 Other hazards

None known.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DOS Thread Locking Agent medium 50g

Version 4.12 Revision Date: 09.11.2020 SDS Number: 576365-00006 Date of last issue: 05.05.2020
Date of first issue: 21.12.2009

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2,6-Di-tert-butyl-p-cresol	128-37-0 204-881-4	Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	$\geq 0.25 - < 1$
Cumene hydroperoxide	80-15-9 201-254-7 617-002-00-8	Org. Perox. E; H242 Acute Tox. 4; H302 Acute Tox. 3; H331 Acute Tox. 2; H310 Skin Corr. 1; H314 Eye Dam. 1; H318 STOT SE 3; H335 STOT RE 2; H373 (Lungs) Aquatic Chronic 2; H411	$\geq 0.25 - < 1$
2'-Phenylacetohydrazide	114-83-0 204-055-3	Acute Tox. 3; H301 Acute Tox. 3; H311 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Carc. 2; H351 Aquatic Acute 1; H400 M-Factor (Acute aquatic toxicity): 1	$\geq 0.1 - < 0.25$

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DOS Thread Locking Agent medium 50g

Version	Revision Date:	SDS Number:	Date of last issue: 05.05.2020
4.12	09.11.2020	576365-00006	Date of first issue: 21.12.2009

- If inhaled : If inhaled, remove to fresh air.
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Nitrogen oxides (NO_x)
Sulphur oxides
Carbon oxides
Fluorine compounds

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DOS Thread Locking Agent medium 50g

Version	Revision Date:	SDS Number:	Date of last issue: 05.05.2020
4.12	09.11.2020	576365-00006	Date of first issue: 21.12.2009

Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Avoid inhalation of vapour or mist.
Do not swallow.
Avoid contact with eyes.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DOS Thread Locking Agent medium 50g

Version 4.12 Revision Date: 09.11.2020 SDS Number: 576365-00006 Date of last issue: 05.05.2020
Date of first issue: 21.12.2009

Avoid prolonged or repeated contact with skin.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Take care to prevent spills, waste and minimize release to the environment.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep in properly labelled containers. Store in accordance with the particular national regulations.

Advice on common storage : Do not store with the following product types:
Strong oxidizing agents

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2,6-Di-tert-butyl-p-cresol	128-37-0	TWA	10 mg/m ³	GB EH40
Further information: Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.				

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
1,2-Benzisothiazol-3(2H)-one 1,1-dioxide	Workers	Inhalation	Long-term systemic effects	4.19 mg/m ³
	Workers	Skin contact	Long-term systemic effects	2.381 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1.035 mg/m ³
2,6-Di-tert-butyl-p-cresol	Consumers	Skin contact	Long-term systemic effects	1.190 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	0.595 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	3.5 mg/m ³
	Workers	Dermal	Long-term systemic	0.5 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DOS Thread Locking Agent medium 50g

Version 4.12 Revision Date: 09.11.2020 SDS Number: 576365-00006 Date of last issue: 05.05.2020
Date of first issue: 21.12.2009

			effects	bw/day
	Consumers	Inhalation	Long-term systemic effects	0.86 mg/m ³
	Consumers	Dermal	Long-term systemic effects	0.25 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0.25 mg/kg bw/day
Cumene hydroperoxide	Workers	Inhalation	Long-term systemic effects	6 mg/m ³

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
1,2-Benzisothiazol-3(2H)-one 1,1-dioxide	Fresh water	0.104 mg/l
	Marine water	0.0104 mg/l
	Intermittent use/release	1.044 mg/l
	Fresh water sediment	104.403 mg/kg
	Marine sediment	104.403 mg/kg
	Soil	29.024 mg/kg
2,6-Di-tert-butyl-p-cresol	Sewage treatment plant	12.304 mg/l
	Fresh water	0.199 µg/l
	Intermittent use/release	0.02 µg/l
	Marine water	0.02 µg/l
	Sewage treatment plant	0.17 mg/l
	Fresh water sediment	0.0996 mg/kg dry weight (d.w.)
	Marine sediment	0.00996 mg/kg dry weight (d.w.)
	Soil	0.04769 mg/kg dry weight (d.w.)
	Oral (Secondary Poisoning)	8.33 mg/kg food
Cumene hydroperoxide	Fresh water	0.0031 mg/l
	Marine water	0.00031 mg/l
	Freshwater - intermittent	0.031 mg/l
	Sewage treatment plant	0.35 mg/l
	Fresh water sediment	0.023 mg/kg dry weight (d.w.)
	Marine sediment	0.0023 mg/kg dry weight (d.w.)
	Soil	0.0029 mg/kg dry weight (d.w.)

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Eye protection : Please follow all applicable local/national requirements when selecting protective measures for a specific workplace.

Wear the following personal protective equipment:
Safety glasses

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DOS Thread Locking Agent medium 50g

Version	Revision Date:	SDS Number:	Date of last issue: 05.05.2020
4.12	09.11.2020	576365-00006	Date of first issue: 21.12.2009

Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.
Equipment should conform to BS EN 166

Hand protection

Material	:	Nitrile rubber
Break through time	:	480 min
Glove thickness	:	> 0.35 mm
Directive	:	Equipment should conform to BS EN 374

Remarks	:	Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
---------	---	---

Skin and body protection	:	Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential. Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
--------------------------	---	---

Respiratory protection	:	If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection. Equipment should conform to BS EN 143
------------------------	---	---

Filter type	:	Particulates type (P)
-------------	---	-----------------------

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Colour	:	blue
Odour	:	mild
Odour Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available
Flash point	:	> 100 °C
Evaporation rate	:	No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DOS Thread Locking Agent medium 50g

Version 4.12 Revision Date: 09.11.2020 SDS Number: 576365-00006 Date of last issue: 05.05.2020
Date of first issue: 21.12.2009

Flammability (solid, gas)	:	Not applicable
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	1.12 g/cm ³ (20 °C)
Solubility(ies)		
Water solubility	:	partly miscible
Partition coefficient: n-octanol/water	:	Not applicable
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	1,500 - 3,000 mPa.s (25 °C) Method: Brookfield
Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.

9.2 Other information

Flammability (liquids)	:	Ignitable (see flash point)
Particle size	:	Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Can react with strong oxidizing agents.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DOS Thread Locking Agent medium 50g

Version 4.12 Revision Date: 09.11.2020 SDS Number: 576365-00006 Date of last issue: 05.05.2020
Date of first issue: 21.12.2009

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Components:

2,6-Di-tert-butyl-p-cresol:

Acute oral toxicity : LD50 (Rat): > 6,000 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Cumene hydroperoxide:

Acute oral toxicity : LD50 (Rat, male): 382 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l
Exposure time: 4 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DOS Thread Locking Agent medium 50g

Version 4.12 Revision Date: 09.11.2020 SDS Number: 576365-00006 Date of last issue: 05.05.2020
Date of first issue: 21.12.2009

Test atmosphere: vapour
Method: Expert judgement
Remarks: Based on harmonised classification in EU regulation 1272/2008, Annex VI

Acute dermal toxicity : LD50 (Rabbit, male): 133.6 mg/kg

2'-Phenylacetohydrazide:

Acute oral toxicity : LD50 (Mouse): 270 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 300 - 2,000 mg/kg
Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

Components:

2,6-Di-tert-butyl-p-cresol:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

Cumene hydroperoxide:

Species : Rabbit
Result : Corrosive after 4 hours or less of exposure

2'-Phenylacetohydrazide:

Species : Rabbit
Result : Skin irritation
Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Not classified based on available information.

Components:

2,6-Di-tert-butyl-p-cresol:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation
Remarks : Based on data from similar materials

Cumene hydroperoxide:

Species : Rabbit
Result : Irreversible effects on the eye

2'-Phenylacetohydrazide:

Species : Rabbit

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DOS Thread Locking Agent medium 50g

Version 4.12 Revision Date: 09.11.2020 SDS Number: 576365-00006 Date of last issue: 05.05.2020
Date of first issue: 21.12.2009

Result : Irritation to eyes, reversing within 21 days
Remarks : Based on data from similar materials

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

2,6-Di-tert-butyl-p-cresol:

Test Type : Human repeat insult patch test (HRIPT)
Exposure routes : Skin contact
Species : Humans
Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

2,6-Di-tert-butyl-p-cresol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)
Species: Rat
Application Route: Ingestion
Result: negative

Cumene hydroperoxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: positive

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)
Result: positive

Test Type: Chromosome aberration test in vitro
Result: positive

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DOS Thread Locking Agent medium 50g

Version 4.12 Revision Date: 09.11.2020 SDS Number: 576365-00006 Date of last issue: 05.05.2020
Date of first issue: 21.12.2009

Species: Mouse
Application Route: Skin contact
Result: negative

2'-Phenylacetohydrazide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: positive

Carcinogenicity

Not classified based on available information.

Components:

2,6-Di-tert-butyl-p-cresol:

Species : Rat
Application Route : Ingestion
Exposure time : 22 Months
Result : negative

2'-Phenylacetohydrazide:

Species : Mouse
Application Route : Ingestion
Exposure time : 2 years
Result : positive

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies (oral)

Reproductive toxicity

Not classified based on available information.

Components:

2,6-Di-tert-butyl-p-cresol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Result: negative

Cumene hydroperoxide:

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DOS Thread Locking Agent medium 50g

Version 4.12 Revision Date: 09.11.2020 SDS Number: 576365-00006 Date of last issue: 05.05.2020
Date of first issue: 21.12.2009

STOT - single exposure

Not classified based on available information.

Components:

Cumene hydroperoxide:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Components:

2,6-Di-tert-butyl-p-cresol:

Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Cumene hydroperoxide:

Exposure routes : Inhalation
Target Organs : Lungs
Assessment : Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

Repeated dose toxicity

Components:

2,6-Di-tert-butyl-p-cresol:

Species : Rat
NOAEL : 25 mg/kg
Application Route : Ingestion
Exposure time : 22 Months

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

Components:

2,6-Di-tert-butyl-p-cresol:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 0.57 mg/l
Exposure time: 96 h
Method: Directive 67/548/EEC, Annex V, C.1.

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.48 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 0.24

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DOS Thread Locking Agent medium 50g

Version 4.12 Revision Date: 09.11.2020 SDS Number: 576365-00006 Date of last issue: 05.05.2020
Date of first issue: 21.12.2009

plants mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (*Pseudokirchneriella subcapitata* (green algae)): 0.24 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) : 1

Toxicity to microorganisms : EC50 : > 10,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Toxicity to fish (Chronic toxicity) : NOEC: 0.053 mg/l
Exposure time: 30 d
Species: *Oryzias latipes* (Japanese medaka)
Method: OECD Test Guideline 210

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.316 mg/l
Exposure time: 21 d
Species: *Daphnia magna* (Water flea)

M-Factor (Chronic aquatic toxicity) : 1

Cumene hydroperoxide:

Toxicity to fish : LC50 (*Oncorhynchus mykiss* (rainbow trout)): 3.9 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): 18.84 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (*Desmodesmus subspicatus* (green algae)): 3.1 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (*Desmodesmus subspicatus* (green algae)): 1 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

2'-Phenylacetohydrazide:

Toxicity to fish : LC50 (*Brachydanio rerio* (zebrafish)): > 0.1 - 1 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

M-Factor (Acute aquatic toxicity) : 1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DOS Thread Locking Agent medium 50g

Version 4.12 Revision Date: 09.11.2020 SDS Number: 576365-00006 Date of last issue: 05.05.2020
Date of first issue: 21.12.2009

12.2 Persistence and degradability

Components:

2,6-Di-tert-butyl-p-cresol:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 4.5 %
Exposure time: 28 d
Method: OECD Test Guideline 301C

Cumene hydroperoxide:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 3 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

2'-Phenylacetohydrazide:

Biodegradability : Result: Readily biodegradable.
Remarks: Based on data from similar materials

12.3 Bioaccumulative potential

Components:

2,6-Di-tert-butyl-p-cresol:

Bioaccumulation : Species: Cyprinus carpio (Carp)
Bioconcentration factor (BCF): 330 - 1,800

Partition coefficient: n-octanol/water : log Pow: 5.1

Cumene hydroperoxide:

Partition coefficient: n-octanol/water : log Pow: 1.6
Method: OECD Test Guideline 117

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Not relevant

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.
Waste codes should be assigned by the user, preferably in

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DOS Thread Locking Agent medium 50g

Version	Revision Date:	SDS Number:	Date of last issue: 05.05.2020
4.12	09.11.2020	576365-00006	Date of first issue: 21.12.2009

discussion with the waste disposal authorities.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

Waste Code : The following Waste Codes are only suggestions:

used product
08 04 10, waste adhesives and sealants other than those mentioned in 08 04 09

unused product
08 04 10, waste adhesives and sealants other than those mentioned in 08 04 09

uncleaned packagings
15 01 06, mixed packaging

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 3

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DOS Thread Locking Agent medium 50g

Version 4.12 Revision Date: 09.11.2020 SDS Number: 576365-00006 Date of last issue: 05.05.2020
Date of first issue: 21.12.2009

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 81 %

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

H242 : Heating may cause a fire.
H301 : Toxic if swallowed.
H302 : Harmful if swallowed.
H310 : Fatal in contact with skin.
H311 : Toxic in contact with skin.
H314 : Causes severe skin burns and eye damage.
H315 : Causes skin irritation.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.
H331 : Toxic if inhaled.
H335 : May cause respiratory irritation.
H351 : Suspected of causing cancer if swallowed.
H373 : May cause damage to organs through prolonged or repeated exposure.
H400 : Very toxic to aquatic life.
H410 : Very toxic to aquatic life with long lasting effects.
H411 : Toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DOS Thread Locking Agent medium 50g

Version 4.12 Revision Date: 09.11.2020 SDS Number: 576365-00006 Date of last issue: 05.05.2020
Date of first issue: 21.12.2009

Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Carc.	:	Carcinogenicity
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Org. Perox.	:	Organic peroxides
Skin Corr.	:	Skin corrosion
Skin Irrit.	:	Skin irritation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

Classification procedure:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DOS Thread Locking Agent medium 50g

Version	Revision Date:	SDS Number:	Date of last issue: 05.05.2020
4.12	09.11.2020	576365-00006	Date of first issue: 21.12.2009

Aquatic Chronic 3

H412

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

GB / EN