

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dieselcure 330ml

Version	Revision Date:	SDS Number:	Date of last issue: 29.04.2020
4.3	14.11.2020	997280-00005	Date of first issue: 26.11.2012

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Dieselcure 330ml
Product code : 0893567330

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Additive
stance/Mixture : Professional use product

1.3 Details of the supplier of the safety data sheet

Company : Würth UK Ltd
1 Centurion Way
Erith, Kent

Telephone : +44 (0)3300 555 444
Telefax : +44 (0)3300 555 666
E-mail address of person : prodsafe@wuerth.com
responsible for the SDS

1.4 Emergency telephone number

+44 (0)870 190 6777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4	H302: Harmful if swallowed.
Acute toxicity, Category 4	H332: Harmful if inhaled.
Acute toxicity, Category 4	H312: Harmful in contact with skin.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Reproductive toxicity, Category 2	H361d: Suspected of damaging the unborn child.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dieselcure 330ml

Version 4.3 Revision Date: 14.11.2020 SDS Number: 997280-00005 Date of last issue: 29.04.2020
Date of first issue: 26.11.2012

- Hazard pictograms :
- Signal word : Warning
- Hazard statements : H302 + H312 + H332 Harmful if swallowed, in contact with skin or if inhaled.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H361d Suspected of damaging the unborn child.
- Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P270 Do not eat, drink or smoke when using this product.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
- Response:**
P302 + P352 + P312 IF ON SKIN: Wash with plenty of water. Call a POISON CENTER/ doctor if you feel unwell.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.

Hazardous components which must be listed on the label:

2-Butoxyethanol
Diethylene glycol methyl ether

2.3 Other hazards

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2-Butoxyethanol	111-76-2 203-905-0 603-014-00-0	Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319	>= 70 - < 90
Diethylene glycol methyl ether	111-77-3 203-906-6 603-107-00-6	Repr. 2; H361d	>= 10 - < 20

Substances with a workplace exposure limit :

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dieselcure 330ml

Version 4.3 Revision Date: 14.11.2020 SDS Number: 997280-00005 Date of last issue: 29.04.2020
Date of first issue: 26.11.2012

(2-Methoxymethylethoxy)propanol	34590-94-8 252-104-2		>= 10 - < 20
---------------------------------	-------------------------	--	--------------

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- If inhaled : If inhaled, remove to fresh air.
If not breathing, give artificial respiration.
If breathing is difficult, give oxygen.
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : Harmful if swallowed, in contact with skin or if inhaled.
Causes skin irritation.
Causes serious eye irritation.
Suspected of damaging the unborn child.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically and supportively.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Diesalcure 330ml

Version	Revision Date:	SDS Number:	Date of last issue: 29.04.2020
4.3	14.11.2020	997280-00005	Date of first issue: 26.11.2012

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dieselcure 330ml

Version	Revision Date:	SDS Number:	Date of last issue: 29.04.2020
4.3	14.11.2020	997280-00005	Date of first issue: 26.11.2012

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapours/mists with a water spray jet.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.

Advice on safe handling : Do not get on skin or clothing.
Avoid breathing mist or vapours.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep container tightly closed.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Do not eat, drink or smoke when using this product.
Take care to prevent spills, waste and minimize release to the environment.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage : Keep in properly labelled containers. Store locked up. Keep

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dieselcure 330ml

Version 4.3 Revision Date: 14.11.2020 SDS Number: 997280-00005 Date of last issue: 29.04.2020
Date of first issue: 26.11.2012

areas and containers tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition.

Advice on common storage : Do not store with the following product types:
Strong oxidizing agents
Explosives
Gases

Recommended storage temperature : > -70 °C

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2-Butoxyethanol	111-76-2	TWA	20 ppm 98 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	50 ppm 246 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	25 ppm 123 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	50 ppm 246 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
Diethylene glycol methyl ether	111-77-3	TWA	10 ppm 50.1 mg/m ³	2006/15/EC
	Further information: Indicative, Identifies the possibility of significant uptake through the skin			
		TWA	10 ppm 50.1 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
(2-	34590-94-8	TWA	50 ppm	2000/39/EC

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dieselcure 330ml

Version 4.3 Revision Date: 14.11.2020 SDS Number: 997280-00005 Date of last issue: 29.04.2020
Date of first issue: 26.11.2012

Methoxymethylethoxy)propanol			308 mg/m ³	
Further information: Identifies the possibility of significant uptake through the skin, Indicative				
		TWA	50 ppm 308 mg/m ³	GB EH40
Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.				

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
2-Butoxyethanol	111-76-2	butoxyacetic acid: 240 Millimoles per mole Creatinine (Urine)	After shift	GB EH40 BAT

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2-Butoxyethanol	Workers	Inhalation	Long-term systemic effects	98 mg/m ³
	Workers	Inhalation	Acute systemic effects	1091 mg/m ³
	Workers	Inhalation	Acute local effects	246 mg/m ³
	Workers	Skin contact	Long-term systemic effects	125 mg/kg bw/day
	Workers	Skin contact	Acute systemic effects	89 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	59 mg/m ³
	Consumers	Inhalation	Acute systemic effects	426 mg/m ³
	Consumers	Inhalation	Acute local effects	147 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	75 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	89 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	6.3 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	26.7 mg/kg bw/day
Diethylene glycol methyl ether	Workers	Inhalation	Long-term systemic effects	50.1 mg/m ³
	Workers	Skin contact	Long-term systemic effects	0.53 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	25 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	0.27 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	1.5 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dieselcure 330ml

Version 4.3 Revision Date: 14.11.2020 SDS Number: 997280-00005 Date of last issue: 29.04.2020
Date of first issue: 26.11.2012

			effects	bw/day
(2-Methoxymethylethoxy)propanol	Workers	Inhalation	Long-term systemic effects	308 mg/m3
	Workers	Skin contact	Long-term systemic effects	238 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	37.2 mg/m3
	Consumers	Skin contact	Long-term systemic effects	121 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	36 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
2-Butoxyethanol	Fresh water	8.8 mg/l
	Marine water	0.88 mg/l
	Freshwater - intermittent	26.4 mg/l
	Sewage treatment plant	463 mg/l
	Fresh water sediment	34.6 mg/kg dry weight (d.w.)
	Marine sediment	3.46 mg/kg dry weight (d.w.)
	Soil	2.33 mg/kg dry weight (d.w.)
	Oral (Secondary Poisoning)	20 mg/kg food
Diethylene glycol methyl ether	Fresh water	12 mg/l
	Marine water	1.2 mg/l
	Intermittent use/release	12 mg/l
	Sewage treatment plant	10000 mg/l
	Fresh water sediment	44.4 mg/kg
	Marine sediment	0.44 mg/kg
	Soil	2.44 mg/kg
(2-Methoxymethylethoxy)propanol	Fresh water	19 mg/l
	Freshwater - intermittent	190 mg/l
	Marine sediment	1.9 mg/l
	Sewage treatment plant	4168 mg/l
	Fresh water sediment	70.2 mg/kg dry weight (d.w.)
	Marine sediment	7.02 mg/kg dry weight (d.w.)
	Soil	2.74 mg/kg dry weight (d.w.)

8.2 Exposure controls

Engineering measures

Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.

Personal protective equipment

Eye protection : Wear the following personal protective equipment:
Safety goggles

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dieselcure 330ml

Version	Revision Date:	SDS Number:	Date of last issue: 29.04.2020
4.3	14.11.2020	997280-00005	Date of first issue: 26.11.2012

Equipment should conform to BS EN 166

Hand protection

Material : Fluorinated rubber
Break through time : \geq 480 min
Glove thickness : 0.4 mm

Material : butyl-rubber
Break through time : \geq 480 min
Glove thickness : 0.5 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection

: Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Respiratory protection

: If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
Equipment should conform to BS EN 14387

Filter type

: Organic vapour type (A)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid
Colour : colourless, clear
Odour : unpleasant
Odour Threshold : No data available
pH : No data available
Melting point/freezing point : -76.92 °C
Initial boiling point and boiling : 171 °C

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Diesalcure 330ml

Version	Revision Date:	SDS Number:	Date of last issue: 29.04.2020
4.3	14.11.2020	997280-00005	Date of first issue: 26.11.2012

range

Flash point	:	72.5 °C	Method: closed cup
Evaporation rate	:	No data available	
Flammability (solid, gas)	:	Not applicable	
Upper explosion limit / Upper flammability limit	:	11.39 %(V)	
Lower explosion limit / Lower flammability limit	:	1.13 %(V)	
Vapour pressure	:	0.8 hPa (20 °C)	
Relative vapour density	:	4.1	
Density	:	0.9112 g/cm ³ (20 °C)	
Solubility(ies)			
Water solubility	:	completely soluble	
Partition coefficient: n-octanol/water	:	Not applicable	
Auto-ignition temperature	:	259 °C	
Decomposition temperature	:	No data available	
Viscosity			
Viscosity, kinematic	:	2.266 mm ² /s (40 °C)	
Explosive properties	:	Not explosive	
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.	

9.2 Other information

Flammability (liquids)	:	No data available
Particle size	:	Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dieselcure 330ml

Version	Revision Date:	SDS Number:	Date of last issue: 29.04.2020
4.3	14.11.2020	997280-00005	Date of first issue: 26.11.2012

Hazardous reactions : Combustible liquid.
Vapours may form explosive mixture with air.
Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Harmful if swallowed, in contact with skin or if inhaled.

Product:

Acute oral toxicity : Acute toxicity estimate: 1,886 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 14.67 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: 1,467 mg/kg
Method: Calculation method

Components:

2-Butoxyethanol:

Acute oral toxicity : LD50 (Guinea pig): 1,414 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Expert judgement
Remarks: Based on harmonised classification in EU regulation 1272/2008, Annex VI

Acute dermal toxicity : Acute toxicity estimate: 1,100 mg/kg
Method: Expert judgement

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dieselcure 330ml

Version 4.3 Revision Date: 14.11.2020 SDS Number: 997280-00005 Date of last issue: 29.04.2020
Date of first issue: 26.11.2012

Remarks: Based on harmonised classification in EU regulation 1272/2008, Annex VI

Diethylene glycol methyl ether:

Acute oral toxicity : LD50 (Rat): 7,128 mg/kg
Acute inhalation toxicity : LC0 (Rat): > 1.2 mg/l
Exposure time: 6 h
Test atmosphere: vapour
Method: OECD Test Guideline 403
Acute dermal toxicity : LD50 (Rabbit): 9,404 mg/kg

(2-Methoxymethylethoxy)propanol:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity : LC0 (Rat): > 1.667 mg/l
Exposure time: 7 h
Test atmosphere: dust/mist
Acute dermal toxicity : LD50 (Rabbit): 9,510 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Components:

2-Butoxyethanol:

Species : Rabbit
Method : Directive 67/548/EEC, Annex V, B.4.
Result : Skin irritation

Diethylene glycol methyl ether:

Species : Rabbit
Result : No skin irritation

(2-Methoxymethylethoxy)propanol:

Species : Rabbit
Result : No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

2-Butoxyethanol:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Irritation to eyes, reversing within 21 days

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dieselcure 330ml

Version 4.3 Revision Date: 14.11.2020 SDS Number: 997280-00005 Date of last issue: 29.04.2020
Date of first issue: 26.11.2012

Diethylene glycol methyl ether:

Species : Rabbit
Result : No eye irritation

(2-Methoxymethylethoxy)propanol:

Species : Rabbit
Result : No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

2-Butoxyethanol:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Diethylene glycol methyl ether:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

(2-Methoxymethylethoxy)propanol:

Test Type : Human repeat insult patch test (HRIPT)
Exposure routes : Skin contact
Species : Humans
Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

2-Butoxyethanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: In vitro mammalian cell gene mutation test

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dieselcure 330ml

Version	Revision Date:	SDS Number:	Date of last issue: 29.04.2020
4.3	14.11.2020	997280-00005	Date of first issue: 26.11.2012

Result: negative

Test Type: In vitro sister chromatid exchange assay in mammalian cells

Result: equivocal

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: Intraperitoneal injection
Result: negative

Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)

Species: Mouse

Application Route: Intraperitoneal injection

Result: negative

Diethylene glycol methyl ether:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

(2-Methoxymethylethoxy)propanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro

Result: negative

Test Type: Saacharomyces cerevisiae, mitotic recombination assay (in vitro)

Result: negative

Carcinogenicity

Not classified based on available information.

Components:

2-Butoxyethanol:

Species : Rat
Application Route : inhalation (vapour)
Exposure time : 2 Years
Result : negative

(2-Methoxymethylethoxy)propanol:

Species : Rat
Application Route : inhalation (vapour)
Exposure time : 2 Years
Method : OECD Test Guideline 453
Result : negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dieselcure 330ml

Version 4.3 Revision Date: 14.11.2020 SDS Number: 997280-00005 Date of last issue: 29.04.2020
Date of first issue: 26.11.2012

Remarks : Based on data from similar materials

Reproductive toxicity

Suspected of damaging the unborn child.

Components:

2-Butoxyethanol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Mouse
Application Route: Ingestion
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Result: negative

Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Diethylene glycol methyl ether:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 416
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Result: positive
Remarks: Based on data from similar materials

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

(2-Methoxymethylethoxy)propanol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Method: OECD Test Guideline 416
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dieselcure 330ml

Version 4.3 Revision Date: 14.11.2020 SDS Number: 997280-00005 Date of last issue: 29.04.2020
Date of first issue: 26.11.2012

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Diethylene glycol methyl ether:

Species : Rat
NOAEL : 900 mg/kg
Application Route : Ingestion
Exposure time : 6 Weeks

(2-Methoxymethylethoxy)propanol:

Species : Rat
NOAEL : 1.21 mg/l
Application Route : inhalation (vapour)
Exposure time : 13 Weeks

Species : Rat
NOAEL : 1,000 mg/kg
Application Route : Ingestion
Exposure time : 4 Weeks

Species : Rabbit
NOAEL : 2,850 mg/kg
Application Route : Skin contact
Exposure time : 90 Days

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

Components:

2-Butoxyethanol:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 1,464 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1,800 mg/l
aquatic invertebrates : Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : ErC50 (Pseudokirchneriella subcapitata (green algae)): 1,840

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dieselcure 330ml

Version 4.3 Revision Date: 14.11.2020 SDS Number: 997280-00005 Date of last issue: 29.04.2020
Date of first issue: 26.11.2012

plants mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

EC10 (Pseudokirchneriella subcapitata (green algae)): 679 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC: > 100 mg/l
Exposure time: 21 d
Species: Danio rerio (zebra fish)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC10: 134 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

Diethylene glycol methyl ether:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 5,741 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1,192 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 : > 1,000 mg/l
Exposure time: 30 min
Method: OECD Test Guideline 209

(2-Methoxymethylethoxy)propanol:

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): > 1,000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1,919 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 969 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 969 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (Pseudomonas putida): 4,168 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dieselcure 330ml

Version	Revision Date:	SDS Number:	Date of last issue: 29.04.2020
4.3	14.11.2020	997280-00005	Date of first issue: 26.11.2012

Exposure time: 18 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: ≥ 0.5 mg/l
Exposure time: 22 d
Species: Daphnia magna (Water flea)

12.2 Persistence and degradability

Components:

2-Butoxyethanol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 90.4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Diethylene glycol methyl ether:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

(2-Methoxymethylethoxy)propanol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 76 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

12.3 Bioaccumulative potential

Components:

2-Butoxyethanol:

Partition coefficient: n-octanol/water : log Pow: 0.81

Diethylene glycol methyl ether:

Partition coefficient: n-octanol/water : log Pow: -0.47

(2-Methoxymethylethoxy)propanol:

Partition coefficient: n-octanol/water : log Pow: 0.004

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Not relevant

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Diesalcure 330ml

Version	Revision Date:	SDS Number:	Date of last issue: 29.04.2020
4.3	14.11.2020	997280-00005	Date of first issue: 26.11.2012

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- Product : Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal. Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product.
- Waste Code : The following Waste Codes are only suggestions:
- used product
20 01 29, detergents containing hazardous substances
 - unused product
20 01 29, detergents containing hazardous substances
 - uncleaned packagings
15 01 10, packaging containing residues of or contaminated by hazardous substances
-

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Diesalcure 330ml

Version	Revision Date:	SDS Number:	Date of last issue: 29.04.2020
4.3	14.11.2020	997280-00005	Date of first issue: 26.11.2012

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

Diethylene glycol methyl ether
(Number on list 54)

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 99.99 %, 300.27 g/l
Remarks: VOC content excluding water

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dieselcure 330ml

Version	Revision Date:	SDS Number:	Date of last issue: 29.04.2020
4.3	14.11.2020	997280-00005	Date of first issue: 26.11.2012

Full text of H-Statements

H302	: Harmful if swallowed.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H361d	: Suspected of damaging the unborn child.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Eye Irrit.	: Eye irritation
Repr.	: Reproductive toxicity
Skin Irrit.	: Skin irritation
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2006/15/EC	: Europe. Indicative occupational exposure limit values
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	: UK. Biological monitoring guidance values
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
2006/15/EC / TWA	: Limit Value - eight hours
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS -

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Diesalcure 330ml

Version	Revision Date:	SDS Number:	Date of last issue: 29.04.2020
4.3	14.11.2020	997280-00005	Date of first issue: 26.11.2012

Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

Acute Tox. 4	H302
Acute Tox. 4	H332
Acute Tox. 4	H312
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Repr. 2	H361d

Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

GB / EN